


DATASHEET

W-CAT-EVBT-001 95mm² BATTERY TEST BOX

A specially designed test box to enable remote electrical safety testing of a 50 VDC electric vehicle DC battery pack.

Special Features

- Specific Test Points for:
 - Voltage test
 - Insulation Test
 - HiPot Test
- Custom HiPot test lead to interface with Seaward HAL103



Functions and benefits

The W-CAT-EVBT-001 is specifically designed to be connected to the mating connectors installed on a 50 VDC battery pack:


- +Ve SLPPC85BSO0
- -Ve SLPPC85BSO1

The cable length of 1m from the connectors to the test box allow the tests to be carried out by the user in a safe and comfortable location away from the battery pack.

The test box has the following test points incorporated:


- 1000V CAT III test points for a Voltage check using RS PRO RS-9331 1000V Voltage Tester
- 1000V CAT III 4mm banana socket test points for an Insulation Test using a Fluke 1587 Insulation Multimeter.
- 5000V CAT 0 4mm banana sockets and W-5600H05-100-0 test lead for an HiPot test using a Seaward HAL103 HiPot tester.

Specifications

W-CAT-EVBT-001 95mm ² Battery Test Box	
	
Cables	
95mm ² Cable	
Type	COROFLEX 180HV SSC - FHLR2GCB2G
Dimensions	Stranded bare copper 3000 (±5%) x max. 0.21 mm Conductor core 17.2mm, Outer sheath 20.9mm Length 1m

Insulation/ cable jacket	Silicone (RAL 2003) min 0.92mm
Shielding	Tinned copper max. 0.26 mm Optical covering min. 85 %
Max wire resistance	0.196 mΩ/m
Voltage	Max 1000 VDC. Test voltage 5.0kV @ 5 mins
Temperature	-40 °C to +180 °C
Internal Connections	
Type	Electro-PJP 9050
Dimensions	Stranded bare copper 644 x Ø0,07 mm Outer diameter 3.7mm
Insulation/ cable jacket	Two silicone jackets. Wire wear indicator
Shielding	None
Max wire resistance	0.798 mΩ/m
Voltage	Insulation resistance greater than 2.2 GΩ @ 1000 VDC CAT IV
Temperature	-60 °C to +180 °C
Test Sockets	
Voltage Test Sockets	
Type	In-built to enclosure lid
Socket dimensions	Socket designed to accept the angles and length of the RS Pro RS-3991 tester probes
Electrical protection	1000V CAT III
Current	36A
Temperature	-20 °C to +80 °C, Pollution degree 2
Materials	Conductors – Stainless steel and copper bar Insulator – Amphora HT3300
Insulation Test Sockets	
Type	Electro-PJP 3274-I
Socket dimensions	Socket accepts shrouded (safety) 4mm banana plugs in accordance with IEC 61010-031
Electrical protection	1000V CAT III
Current	36A
Temperature	-20 °C to +80 °C, Pollution degree 2
Materials	Conductors – Nickel coated brass Insulator – Polypropylene
HiPot Test Sockets	
Type	Electro-PJP 5274-HT
Socket dimensions	Socket accepts Electro-PJP 4mm Banana Plug 5600-HT
Electrical protection	5000V CAT 0 (transient overvoltage of 2Kv), 1000V CAT IV
Current	10A
Temperature	-20 °C to +80 °C, Pollution degree 2
Materials	Conductors – Nickel coated brass Insulator – Polypropylene
HiPot Test Lead	
Type	Warwick Test Supplies W-5600H05-100-0
Dimensions	5600-HT Plug 110mm long, 28mm dia finger guard Cable length 1m
Electrical protection	5000V CAT0 (transient overvoltage of 2Kv), 1000V CAT IV
Current	10A
Temperature	-20 °C to +80 °C, Pollution degree 2
Materials	Conductors – Nickel coated brass Insulator – Polypropylene
Enclosure	
Materials	3d Printed Eastman Amphora HT3300
Impact strength	Charpy Notch, ISO 179 3.3 kJ/m ²
Dimensions	L200xW97xD71mm

Dimensions



Warwick Test Supplies Ltd
Ascot II, Wallops Wood
Sheardley Lane
Southampton, SO32 3QY
United Kingdom

www.warwickts.com - +44 (0)1455 558541

Subject to modifications. All product descriptions are for general information only. They are not to be understood as a guarantee of quality or durability